



Specifications Multipack 4x Ledvance  
Waterproof Batten Damp Proof FLEX  
Throughwiring 42W 6900lm - 865  
Daylight | 150cm - Replaces 2x58W

[View Product](#)

General Information

|                          |                                                     |
|--------------------------|-----------------------------------------------------|
| SKU                      | 257744                                              |
| EAN                      | 8719157069243                                       |
| Manufacturer Code        | 8719157069243                                       |
| Brand                    | Ledvance                                            |
| Manufacturer Name        | Multipack 4x DP FLEX TH 1500 P 42W ML 865 IP66 LEDV |
| Any Lamp all-in warranty | 5 Years                                             |
| Average Lifetime (h)     | 100000                                              |

Technical Information

|                             |                |
|-----------------------------|----------------|
| Technology                  | LED Integrated |
| Replaces (Watt)             | 2x58           |
| Wattage                     | 42W            |
| Voltage (V)                 | 220-240        |
| Dimmable                    | Not Dimmable   |
| Colour of Light             | White          |
| Colour Code                 | 865 Daylight   |
| Colour temperature (Kelvin) | 6500 Daylight  |
| Colour Rendering (Ra)       | 80-89          |
| Light colour options        | Single Color   |
| Luminous Flux (Lumen)       | 6900lm         |

|                          |                       |
|--------------------------|-----------------------|
| Luminous Efficacy (lm/W) | 164                   |
| Power factor             | >0.90                 |
| Length                   | 150cm                 |
| Product Type Category    | LED Waterproof Batten |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Surface                |
| Fixture Connection     | PI [Push-in connector] |
| Optical Cover          | Opal                   |
| IP-rating              | IP66                   |
| Impact Protection (IK) | IK08 - 5 joules        |
| Operating Temperature  | -30 to +50             |
| Housing                | PC (Polycarbonate)     |
| Colour of the Fixture  | Grey                   |
| Emergency Lighting     | No Emergency Unit      |

## Dimensions

|             |      |
|-------------|------|
| Length (mm) | 1590 |
| Width (mm)  | 88   |
| Height (mm) | 73   |

## Sensor Information

Type of sensor

**Why Any-lamp?**  
No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

